




## TMC TRAILER AXLES

Besides the full range of standard models, both drum and disc braked, to suit 17.5", 19.5", 22.5" wheels, TMC can offer any axle track length required and can also customize the axle build as necessary to suit special purpose applications.

Whether supplied with 10 tonne **LMV** or 12 tonne **LM Xp** airbag suspension or TMC's well proven mechanical suspension kits, TMC's trailer axles are equipped to return increased profit to the operator through the use of long life components and lower maintenance costs.

- Fully enclosed camshafts
- Induction hardened bearing journals
- Industry standard bearings and seals
- Heavy-duty camshafts to suit all applications
- 'Q' quick release brake shoes
- Quality hub/drum assemblies
- Optional axle tube thickness
- Optional track lengths


# TRAILER AXLES



AXLE TYPE	BRAKE SIZE	HUB	TRACK	ADR RATING
<b>STANDARD TRAILER AXLE - TN WHEEL BEARINGS - HM218248/218210 &amp; HM212049/212011</b>				
851100	420mmx180mm 'S' cam	5 Spoke Spider	1850mm	12.0T
851200	420mmx180mm 'S' cam	10 Stud x 285 pcd	1850mm	12.0T
851250*	420mmx180mm 'S' cam	10 Stud x 285 pcd Alloy	1850mm	12.0T
851300	420mmx180mm 'S' cam	10 Stud x 335 pcd	1850mm	12.0T
851350*	420mmx180mm 'S' cam	10 Stud x 335 pcd Alloy	1850mm	12.0T
851400	335mmx210mm 'S' cam	8 Stud 275 pcd	1860mm	11.5T
851450*	335mmx210mm 'S' cam	8 Stud 275 pcd Alloy	1860mm	11.5T
851600	335mmx210mm 'S' cam	10 Stud 225 pcd	1850mm	11.5T
851700	335mmx210mm 'S' cam	3 Spoke Spider suit 17.5"	1905mm	11.5T
<b>HEAVY DUTY TRAILER AXLE - TP WHEEL BEARINGS - HM518445/518410</b>				
852100	420mmx180mm 'S' cam	5 Spoke Spider	1850mm	12.0T
852200	420mmx180mm 'S' cam	10 stud x 285 pcd	1850mm	12.0T
852300	420mmx180mm 'S' cam	10 Stud 335 pcd	1850mm	12.0T
<b>DISC BRAKE AXLE - TN WHEEL BEARINGS - HM218248/218210 &amp; HM212049/212011</b>				
853100	377mm Diameter / Pan-19	5 Spoke Spider	1850mm	12.0T
853200	377mm Diameter / Pan-19	10 Stud x 285 pcd	1850mm	12.0T
853300	377mm Diameter / Pan-19	10 Stud x 335 pcd	1850mm	12.0T
853400	377mm Diameter / Pan-19	8 Stud x 275 pcd	1850mm	12.0T
<b>DISC BRAKE AXLE - TN WHEEL BEARINGS - HM218248/218210 &amp; HM212049/212011</b>				
855200	430mm Diameter / Pan-22	10 Stud x 285 pcd	1850mm	16.0T
855250*	430mm Diameter / Pan-22	10 Stud x 285 pcd Alloy	1850mm	16.0T
855300	430mm Diameter / Pan-22	10 Stud x 335 pcd	1850mm	16.0T

\*NOTE: AXLES MARKED WITH ASTERISK ARE FITTED WITH CONMET ALLOY HUBS & PRESET BEARINGS

ADR / SARN APPROVALS: - 28815 = Drum Brake 420mm x 180mm 'S' cam / Rating 12.0 Tonne  
 35044 = Drum Brake 335mm x 210mm 'S' cam / Rating 11.5 Tonne  
 30314 = Disc Brake 377mm Rotor / Pan-19 / Rating 12.0 Tonne  
 35045 = Disc Brake 430mm Rotor / Pan-22 / Rating 16.0 Tonne



For extended warranty and lower life cycle cost, TMC's trailer axles – either drum or disc braked – can now be specified with alloy hubs and preset bearings, proven technology from ConMet USA.



For a significantly lower tare weight, TMC drum braked 10 stud 285 pcd axles can be equipped with ConMet's CastLite brake drums.

**TRAILER AXLE SPECIFICATIONS**

TMC Australia Pty Ltd.

78 Star Crescent, PO Box 5028, Hallam, Victoria 3803, Australia. Ph 03 8786 3688, Fax 03 8786 3699, Email info@tmcaus.com.au

TMC Axle Manufacturing Sdn Bhd.

No 79 & 80 Jalan 5/10B, Spring Crest Industrial Park, 68100 Batu Caves, Kuala Lumpur, Malaysia. Ph 03 6187 7788 Fax 03 6187 6722 Email trumas@tm.net.my

A member of The **Trumas** Group

Due to our policy of continuous R&D, we reserve the right to amend specifications without notice or obligation.